

### 01 Chemical Product and Company Identification

<b>Product Name</b>	Formula 324
<b>Product Use</b>	Laundry Stain Removeer
<b>Product Code</b>	3019
<b>For Medical Emergency</b>	Call 'Chemtrec' 1-800-424-9300
<b>Supplier's Information</b>	Santec Inc. 1420 East Linden Avenue, Linden NJ 07036

### 02 Hazards Identification

**GHS Classification:**

1. Skin - Category 1
2. Eyes - Category 1
3. Aspiration Hazard - Category 2

**GHS Label Elements:**



**Signal Word:** Danger

**Hazard Statement:** Causes severe skin burns and eye damage, harmful if swallowed.

**Precautionary Statements:** Wear protective gloves, splash goggles and vapor respirator if necessary. Do not breathe mist /vapors /spray. Wash thoroughly after handling.

**Acute Effects**

**Eyes:** Causes serious eye damage.

**Skin:** Skin contact may produce burns.

**Inhalation:** Irritating to respiratory tract, symptoms include coughing, choking or shortness of breath.

**Ingestion:** Harmful is swallowed. May cause burns to mouth, throat and stomach.

**Chronic Effects**

**Carcinogenicity:** No known critical effects or critical hazards.

**Product /Ingredient Name:** Not available.

### 03 Composition/ Information on Ingredients

Name of Hazardous Ingredients	CAS No.	WT.%
Oxalic Acid, Dihydrate	6153-56-6	10-15
Monoethanolamine	141-43-5	5-10

### 04 First Aid Measures

**Eye Contact:** Check for and remove any contact lenses. Flush with large quantities of water, holding eyelids open for 15 minutes. Seek medical attention immediately.

**Skin Contact:** Wash skin with copious amounts of water. Seek medical attention immediately.

**Inhalation:** Remove to fresh air. Seek medical attention immediately.

**Ingestion:** Do not induce vomiting. Drink copious amounts of water. Seek medical attention immediately.

### 05 Fire Fighting Measures

**Suitable Fire Extinguishing Media:** Use water spray, fog or foam

**Specific Hazards Arising from the Chemical:** None.

**Hazardous Thermal Decomposition Products:** Carbon oxides (CO, CO<sub>2</sub>).

**Specific Fire-Fighting Methods:** Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

**Specific Protective Equipment for Fire-Fighters:** Fire-Fighters should wear appropriate protective equipment and self contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

### 06 Accidental Release Measures

**Spill Clean Up:** Put on appropriate personal protective equipment (see section 8). Stop leak if without risk. Move Containers from spill area. Dilute with water and mop up if water-soluble or absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

### 07 Handling and Storage

**Handling:** Put on appropriate personal protective equipment (see Section 8). Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Do not reuse container. Wash thoroughly after handling.

**Storage:** Store between the following temperatures: 4.44 to 48.9°C (40 to 120°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Separate from acids. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

### 08 Exposure Controls/ Personal Protection

#### Ingredient Name

Oxalic Acid  
Monoethanolamine

#### Exposure Limits

OSHA PEL TWA 1 mg/m<sup>3</sup>  
OSHA PEL 6 mg/m<sup>3</sup>

#### Personal Protective Equipment (PPE)

**Eyes:** Splash goggles. Face shield.

**Skin:** Use synthetic apron, other protective equipment as necessary to prevent skin contact.

**Body:** Face shield, full suit, vapor respirator, boots and gloves.

**Respiratory:** A self contained breathing apparatus should be used to avoid inhalation of product. Be sure to use an approved /certified respirator or equivalent.

### 09 Physical and Chemical Properties

<b>Physical State</b>	Clear liquid
<b>Color</b>	Water White
<b>Odor</b>	Mild
<b>pH</b>	1.6-2.4
<b>Flash point</b>	None
<b>Explosion limits</b>	Not available
<b>Flammability (solid, gas)</b>	Not available
<b>Melting point</b>	Not available
<b>Boiling point</b>	>100°C (212F)
<b>Evaporation rate (butyl acetate = 1)</b>	Not available
<b>Vapor pressure</b>	Not available
<b>Vapor density</b>	Not available
<b>Relative density</b>	1.04 (Water = 1)
<b>Solubility</b>	Easily soluble in the following materials: cold water and hot water
<b>Partition coefficient n-octano/water</b>	Not available
<b>Auto-ignition temperature</b>	Not available
<b>Decomposition temperature</b>	Not available
<b>Odor threshold</b>	Not available
<b>Viscosity</b>	Kinematic (room temperature): ≤ 10 cSt (CPS)

### 10 Stability and Reactivity

**Stability:** The product is stable.

**Possibility of hazardous reactions:** Under normal conditions of storage and use, hazardous reactions will not occur.

**Conditions to avoid:** Avoid moisture.

**Materials to avoid:** Oxidizing agents, alkalis.

**Hazardous decomposition products:** Carbon oxides (CO, CO<sub>2</sub>).

### 11 Toxicological Information

Product /Ingredient Name	Result	Species	Dose
Oxalic Acid	LD50 Oral	Rat	1080 mg/kg
Monoethanolamine	LD50 Oral	Rat	1090 - 3320 mg/kg

### 12 Ecological Information

N/A

### 13 Disposal Considerations

**Waste Information**  
Waste must be disposed of in accordance with federal, state and local environmental control regulations. Consult your local or regional authorities for additional information.

### 14 Transport Information

Regulatory Information	UN Number	Proper Shipping Name	Classes	PG*	Label
<b>DOT Classification</b>	UN3265	Corrosive liquid, acid, inorganic, n.o.s (oxalic acid)	8	II	8 (6.1)
If product sold only in quarts	not regulated	-	-	-	-

**Note:** DOT classification applies to most package sizes. For specific container size classifications or size exceptions, refer to the bill of lading with your shipment.

**PG\*:** Packing Group

### 15 Regulatory Information

**U.S. Federal Regulations**

**TSCA 8(b) inventory:** All components are listed or exempted.

**SARA 302/304/311/312 extremely hazardous substances:** No listed substance

**SARA 302/304 emergency planning and notification:** No listed substance

SARA 313	Product name	CAS number	Concentration
Form R-Reporting requirements	No listed substance		

### 16 Other Information

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy of completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

**Date of Issue: 06/21/2016**

\*Hazard Determination System (HDS):

<b>Health</b>	<b>3</b>
<b>Reactivity</b>	<b>0</b>
<b>Flammability</b>	<b>0</b>

\*NOTE: Hazard Determination System (HDS) ratings are based on a 0-4 rating scale, with 0 representing minimum hazards or risks, and 4 representing significant hazards or risks. Although these ratings are not required on SDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HDS ratings are to be used with a fully implemented program to relay the meanings of this scale.